



PC1800F SERIES (60A/80A)

MPPT Solar Charge Controller

Shenzhen Must Energy Technology Co.,Ltd.

Tel: +86 755-29022692, 29101136

Email: sales@must-solar.com

Web: www.must-solar.com

MUST[®]

MUST®

PC1800F Series (60A/80A) MPPT Solar Charge Controller



INTRODUCTION

MPPT (Maximum Power Point Tracking) Solar Charge Controller offer an efficient, safe, multi-stage recharging process that prolongs battery life and assures peak performance from a solar array. Each Charge Controller allows customized battery recharging.

FEATURES

- LCD display , easy to operate on LCD screen
- Multi stage charging (3-stage charging , parallel charging and equalized charging function)
- BTS - Battery remote temperature sensor terminal
- Enable to charge Li-thium, Gel , lead-acid battery
- With RS485 & USB communication port
- Protection: PV array short circuit, PV reverse polarity, Battery reverse polarity, Over charging, Output short circuit



Max charging current
60A to 80A



Radiating mode
Fan cooling



Multi protection



Battery smart
charge design



Battery DC voltage
12V/24V/48V (Auto detection)
36V (Setting)



Peak conversion efficiency:98%
(MPPT Efficiency 99%)




Charging set points
Absorption stage
Float stage

PC1800F Series (60A/80A) MPPT Solar Charge Controller

EQUALIZE STAGE CHARGING FUNCTION

Equalization function reverses the buildup of negative chemical effects like stratification, a condition where acid concentration is greater at the bottom of the battery than at the top. Equalization also helps to remove sulfate crystals that might have built up on the plates.



BATTERY REVERSE PROTECTION


There's a battery reverse protection function in the board, then the controller will be perfectly protected even installer or user connect the battery in reverse pole accidentally

APPLICABLE PLACE


The solar charge controller is an automatic control device, it can be used in all solar power systems to control solar panel array to charge batteries.

Solar Inverter System Connection:

Power Inverter + Solar Charge Controller + Battery + Solar Panels + Grid + Application Loads



PC1800F Series (60A/80A) MPPT Solar Charge Controller



- | | | |
|--------------------------------|--|------------------------------|
| 1. LCD display | 5. Operation button | 9. Wiring box cover |
| 2. Power ON/Charging indicator | 6. PV connextors | 10. RS485 communication port |
| 3. Fault and warning indicator | 7. Battery connectors | 11. USB |
| 4. Wiring fault indicator | 8. Battery temperature sensor terminal | |

MODEL		PC18-6015F		PC18-8015F	
Nominal Battery System Voltage		12V/24V/48VDC (Auto detection); 36V (Setting)			
CONTROLLER INPUT	Battery Voltage	12V	24V	36V	48V
	Maximum Solar Input Voltage	100V	145V		
	PV Array MPPT Voltage Range	15~95V	30~130V	45~130V	60~130V
	Maximum Input Power	12Volt-940W 24Volt-1880W 36Volt-2820W 48Volt-3760W		12Volt-1250W 24Volt-1880W 36Volt-2820W 48Volt-3760W	
BATTERY	Charging Set Points	Absorption Stage		Float Stage	
	Flooded Battery	14.2V/28.4V/42.6V/56.8V		13.7V/27.4V/41.1V/54.8V	
	AGM / GEL / LEAD Battery (Default)	14.4V/28.8V/43.2V/57.6V		13.7V/27.4V/41.1V/54.8V	
	Over-charging Voltage	15.5V/30.0V/45.0V/60.0V			
	Over-charging Comeback Voltage	14.5V/29.5V/44.5V/59.0V			
	Battery Defect Voltage	10.0V/17.0V/25.5V/34.0V			
	Temperature Compensation Coefficient	-5mv / °C /cell (25°C vef)			
	Peak Conversion Efficiency	98% (MPPT Efficiency 99%)			
Max Charging Current	60amps continuous @ 40°C ambient		80amps continuous @ 40°C ambient		
GENERAL SPECIFICATION	Radiating Mode	Fan cooling			
DISPLAY & PROTECTION	Protections	Solar high voltage disconnect Solar high voltage reconnect Battery high voltage disconnect Battery high voltage reconnect High temperature disconnect High temperature reconnect			
MECHANICAL SPECIFICATIONS	Mounting	Wall mount			
	Machine Dimension (W*H*D)	152*85*294 mm (per pcs)			
	G.W (kg)	3kg/pcs			
	Package Dimension (W*H*D)	625*366*232 mm (4pcs / Carton)			
	Gross Weight (kg)	17.4kg (per carton)		19kg (per carton)	
OTHER	Environmental Rating	Indoor			
	Operation Temperature Range	-25~55°C			
	Ambient Humidity	0~90% relative humidity (non-condensing)			
	Altitude	≤3000m			
	Loading (20GP/40GP/40HQ)	3000pcs / 6000pcs / 7200pcs			